



BE NICE TO PEOPLE

FLOORPUL

INTERNATIONAL NV

BELGIUM

live



RUBY 45



RUBY 55



JADE 50



JADE 55



Wheels with big diameter
Große Räder



Digital control board
Digitale Anzeigung



Parabolic squeegee
Parabolische Saugdüse



Big suction filter
Große Saugfilter

Technical data - Technische Daten

	U.M.	RUBY 45	RUBY 55	RUBY 45E	RUBY 55E	JADE 50	JADE 55
Working width Arbeitsbreite	mm	450	550	450	550	500	550
Squeegee width Saugdüsenbreite	mm	790	790	790	790	790 ou/ of 840	790 ou/ of 840
Working capacity Stundenleistung	m ² /h	1575	1925	1575	1925	1800	2000
Brush diameter Durchmesser bürste	mm	2x235	2x285	2x235	2x285	1x508	2x285
Brush speed Bürstendrehzahl	Tr/mn	350	280	350	280	165	370
Brush pressure Druck der bürste	kg	22,5 max	24,5 max	22,5 max	24,5 max	40 max	40 max
Brush motor Bürstenmotor	W	420	420	1000	1000	600	600
Traction motor Fahrtrieb	W	-	-	-	-	150	150
Traction type Antrieb typ		semi-aut.	semi-aut.	semi-aut.	semi-aut.	AUT.	AUT.
Speed Geschwindigkeit	km/h	3,5	3,5	3,5	3,5	4,5	4,5
Max. sloping allowance Max. Steigfähigkeit		2%	2%	2%	2%	10%	10%
Suction motor Saugmotor	W	480	480	600	600	480	480
Depression Vakuum	mbar	120	120	120	120	120	120
Solution tank Laugentank	l	35	35	42	42	53	53
Recovery tank Schmutzwassertank	l	45	45	45	45	56	56
Machine length Maschinenlänge	mm	1102	1140	1102	1140	1335	1272
Machine height Maschinenhöhe	mm	1033	1033	1033	1033	1078	1078
Machine width (without squeegee) Maschinenbreite (ohne Saugdüse)	mm	527	586	527	586	590	604
Batterie capacity (maintenance free) Batterie Kapazität (unterhalts frei)	V/Ah5h	24/118Ah 3h	24/118Ah 3h	-	-	24V/195Ah 4h	24V/195Ah 4h
Batterie weight Gewicht batterien	V/Ah5h	24/75Ah 2h	24/75Ah 2h	-	-	24V/120Ah 2h	24V/120Ah 2h
Battery compartment (Tool box for «E» machines) Batterie Kompartiment (Werkzeug kasten für "E")	kg	55	55	-	-	144	144
Machine weight (without battery) Machinengewicht (ohne batterien)	mm	340x360x300	340x360x300	340x360x120	340x360x120	395x405x374	395x405x374
Noise level (in conformity with IEC 704/1) Schallpegel (conform IEC 704/1)	kg	71	74	72	74	101	100
Vibration level Vibrations niveau	dB(A)	67	67	66,2	66,2	67	67
Classe Classe	m/sc	1.00	1.00	0.86	0.86	1	1
Protection grade Schütz Grad		III	III	I	I	III	III
Voltage Volt	IP	x3	x3	x3	x3	x3	x3
	V	24	24	230V/50Hz	230V/50Hz	24	24